

GENTLE PUMPING FOR ALL WINERY APPLICATIONS

> WAUKESHA ECP PUMP

DIMENSIONS 040/130

Height	Width	Length
86/97cm	55/55cm	108/140cm

Gentle Pump with low life cycle cost

The Waukesha ECP pump is one of the most gentle pumps available. Suitable for most winery applications including pumping high solids and shear sensitive products.

Stator and rotor are stainless steel eliminating problems created by dry running of pumps.

040 - 2" fittings - nominal flow rate of 6,000 l/hr

060 - 2 1/2" fittings - nominal flow rate of 18,000 l/hr

130 - 3" fittings - nominal flow rate of 30,000 l/hr

Features

- Heavy duty stainless steel trolley.
- Puncture proof foam filled tyres on plastic rims (eliminates corrosion).
- Lenze AC Tech wash down variable speed drive.
- SEW geared motor.
- Compact footprint.
- Can be run dry without costly damage to product or pump.
- Standard design pressure rating up to 5 bar.
- Can be supplied for pressures up to 10 bar.
- O ring shaft seals are easy and cheap to replace.
- Low life cycle cost.

Options:

- Pressure control automation package for barrel work, filtration etc.
- Rapidfil heavy duty remote pendant with special polyurethane cable.
- Fail safe radio telemetry system for feeding centrifuges, 300m range.
- Fail safe, hand held radio remote pendant for on, off, direction and speed control up to 100m range.
- Cellar-Mate upgrade.

There is a better way

Rapidfil Pty Ltd

30b Korong Road, Heidelberg West, Vic, 3081, Australia

Telephone 03 9455 3339

Facsimile 03 9459 5232

Email rapidfil@rapidfil.com.au

Web www.rapidfil.com.au

ABN 69 097 700 288

ACN 097 700 288

TECHNICAL DETAILS SUBJECT TO CHANGE WITHOUT NOTICE

The logo for Rapidfil Pty Ltd, featuring the word "rapidfil" in a stylized, lowercase, purple font with a white outline, followed by a white chevron symbol pointing to the right. The logo is set against a dark purple oval background.