

# CABLE PENDANT FOR PUMPS

## > CABLE PENDANT

DIMENSIONS		
Height	Width	Depth
240mm	65mm	50mm

### Cable operated Pendant for Pumps

Industrial product engineered to withstand the rigors of winery cellar operations.

Designed specifically to meet the needs of winery pumps.

Heavy duty construction with inbuilt magnet.

#### Features:

- Housing machined from solid acetyl (industrial plastic).
- O-ring seals on body with 6 stainless steel screws.
- Two latching stainless steel pushbuttons;
  - ◊ Top button for start/stop, depressed position is on.
  - ◊ Bottom button for for/rev, depressed position is reverse.
- IP65 Potentiometer (speed control), with engraving for % reference.
- Recess for button's and potentiometer ensure that damage is minimized when dropped.
- Inbuilt super magnet to clip onto barrel rings and catwalks.
- Stainless steel hook.
- 15m of class 6 polyurethane cable with high abrasion resistance, designed for multiple bending cycles.
- Strain relief on cable gland avoids stress at cable entry.
- Recess on rear to allow a comfortable fit in palm.

#### Set up:

Latched signal for run.

Latched signal for direction On = reverse Off = forward.

0-10V using 2.2kOhm potentiometer for speed control.

0-5V using 1kOhm potentiometer.



rapidfil >

There is a better way

Rapidfil Pty Ltd

30b Korong Road, Heidelberg West, Vic, 3081, Australia

Telephone 03 9455 3339

Facsimile 03 9459 5232

Email [rapidfil@rapidfil.com.au](mailto:rapidfil@rapidfil.com.au)

Web [www.rapidfil.com.au](http://www.rapidfil.com.au)

ABN 69 097 700 288

ACN 097 700 288

TECHNICAL DETAILS SUBJECT TO CHANGE WITHOUT NOTICE