

INNOVATIVE BARREL FILLING AND EMPTYING

>FMT-01



DIMENSIONS

Height	Width	Length	Weight
1100mm	550mm	530mm	35kg

FEATURES

- Two stage filling and emptying cycles, slow fill cycle for topping.
- One filling head fitted with 15m of 1 1/2" hose. Adjustable level sensors allow setting of fast and slow shut off for efficient and accurate filling.
- One emptying head fitted with 15m of 1 1/2" hose. Adjustable level sensors allow setting of fast and slow shut off to leave minimum residue without sucking air into spear.
- One topping head with 15m of 5/8" hose and adjustable level sensor.
- All wiring to heads encapsulated inside hoses for protection and reliability. Conduit entry points sealed with specially designed sanitary fittings.
- All heads are interchangeable and fitted with auto detect feature.
- Self setting safety timer.
- Strainer on inlet to trap seeds and stalks.
- Pump can be plugged into cabinet and controlled via PLC program.
- Unit fitted with lockable stainless steel castors.
- In excess of 30 barrels can be filled in one hour with one operator.
- Up to 25 barrels per hour can be emptied with one operator.
- Full stainless steel construction.

OPTIONS

- 1 1/2" solenoid valve available to reduce restriction through manifold.
- Tandem butterfly valve design available to eliminate strainer and improve hygiene.

There is a better way

Rapidfil Pty Ltd

30B Korong Road Heidelberg West Victoria Australia 3081
Telephone +61 (0)3 9455 3339 Facsimile +61 (0)3 9459 5232
Email rapidfil@rapidfil.com.au Web www.rapidfil.com.au

ABN 69 097 700 288 ACN 097 700 288

THE RAPIDFIL WINE BARREL FILLING UNIT HAS A PATENT APPLICATION PENDING.

rapidfil >