

INNOVATIVE BARREL FILLING AND EMPTYING

>AUTOMATIC TOPPING UNIT

DIMENSIONS			
Height	Width	Length	Weight
1300mm	630mm	1460mm	95kg



FEATURES

- Topping Head fitted with up to 30m of hose.
- Adjustable level sensor allows precise setting of required fill height.
- Compact design, can be supplied to fit between standard USA 3" barrel racks.
- Barrels can be topped precisely in situ without pulling down racks.
- Mobile unit can be easily moved through barrel cellar.
- Cordless operation - operates from DC battery pack. Recharged overnight or operated off 240V AC power. Batteries rated in excess of 8 hours continuous operation
- Self Contained - gas bottle and stainless steel pressure vessel are safely mounted on the unit.
- Audible buzzer to indicate end of cycle.
- Pilot light indicates fill status.
- Precise fill height regardless of barrel size, shape or thickness of stave.
- Heavy duty full stainless steel construction
- Pressurised tank volumes up to 106 litres. Larger volumes can be catered for on special order.
- Electrical wiring to topping head is encapsulated inside hose for protection and reliability. Conduit entry points sealed with specially designed sanitary fittings.

There is a better way

Rapidfil Pty Ltd

30B Korong Road Heidelberg West Victoria Australia 3081
Telephone +61 (0)3 9455 3339 Facsimile +61 (0)3 9459 5232
Email rapidfil@rapidfil.com.au Web www.rapidfil.com.au
ABN 69 097 700 288 ACN 097 700 288

US PATENT 6,871,678

Technical details subject to change

rapidfil >